

Metal forming hosford solution Textbook

plate rolling machine calculation

The process of designing and operating a plate rolling machine requires precise calculations to ensure safety, efficiency, and quality of the rolled plates. Plate rolling machines, also known as plate bending rolls, are essential equipment in manufacturing industries, including shipbuilding, pressure vessel fabrication, and structural steel fabrication. Accurate calculations help determine the machine's capacity, the required roll dimensions, and the operational parameters needed to produce plates with the desired curvature and dimensions. This article provides an in-depth overview of the fundamental calculations involved in selecting and operating a plate rolling machine, emphasizing the importance of understanding material properties, machine parameters, and process variables.

Understanding the Basics of Plate Rolling

Before diving into calculations, it's crucial to understand the basic principles of plate rolling.

What is Plate Rolling?

Plate rolling involves passing a flat sheet of metal through a set of rolls to form a curved or cylindrical shape. Depending on the number of rolls and their arrangement, the process can produce various shapes, including cones and arches.

Types of Plate Rolling Machines

- Three-roll plate rolling machines: Typically include two horizontal rolls and one vertical, allowing for the formation of cylinders and cones.
- Four-roll plate rolling machines: Provide enhanced control and symmetry, suitable for larger and more complex shapes.
- Horizontal and vertical configurations: Based on the orientation of the rolls, influencing the calculation parameters.

Key Parameters in Plate Rolling

- Plate thickness (t)
- Plate width (b)

- Radius of curvature (R)
- Roll diameter (D)
- Roll gap (gap between rolls)
- Material properties (yield strength, Young's modulus)
- Machine capacity (maximum load, maximum roll force)

Fundamental Calculations for Plate Rolling

Calculations in plate rolling focus on determining the required roll dimensions, the force needed to bend the plate, and the machine's capacity to handle the specified work.

Calculating the Minimum Roll Diameter

The roll diameter influences the bending radius achievable and the quality of the rolled plate.

Formula:

$$D_{\min} = \frac{t}{\sin\{\theta\}}$$

Where:

- $D_{\min}$ = minimum roll diameter
- t = plate thickness
- θ = bending angle per pass (typically 30°-60°)

Alternatively, a more conservative approach uses:

$$D_{\min} \approx 6 \times t$$

This ensures the rolls are sufficiently large to prevent cracking and achieve smooth bending.

Considerations:

- Larger rolls produce a gentler bend.
- Smaller rolls allow tighter curves but increase risk of material cracking.

Calculating the Bending Force

The force required to bend the plate is critical for selecting the appropriate machine and ensuring

safety.

Basic Formula:

$$F = \frac{K \times E \times I}{R}$$

Where:

- F = bending force
- K = coefficient depending on material and process (typically 1.2-2)
- E = Young's modulus of the material
- I = moment of inertia of the plate cross-section
- R = desired radius of the bend

For a flat plate:

$$I = \frac{b \times t^3}{12}$$

Simplified Force Calculation:

$$F = \frac{E \times b \times t^2}{R} \times \text{factor}$$

where the factor accounts for material ductility and process safety margins.

Practical Calculation:

- Determine the maximum bending force considering the maximum allowable stress.
- Use the following approximate formula:

$$F_{\max} = \sigma_{\text{allow}} \times A$$

where:

- σ_{allow} = permissible stress (often 0.6-0.8 times yield strength)
- A = cross-sectional area ($b \times t$)

Determining the Roll Force Capacity

The machine must be capable of exerting the calculated force without failure.

Calculation:

- Based on the roll diameter (D) , the maximum roll force $(F_{\max})$ can be related to the roll torque (T) :

$$T = F \times \frac{D}{2}$$

- The machine's roll force capacity should be at least equal to or greater than the calculated force.

Safety Margin:

- It's recommended to include a safety margin of 20-30% to account for material inconsistencies and process variations.

Additional Calculations for Process Optimization

Beyond basic force and dimension calculations, various other parameters influence the final outcome.

Number of Passes

Many plates require multiple passes to achieve the desired curvature with minimal stress.

Estimating Passes:

$$\text{Number of passes} = \frac{\text{Total bending angle}}{\text{Incremental bend per pass}}$$

Incremental bend per pass is often limited to 15° - 20° to prevent cracking.

Material Springback

Springback is the elastic recovery after bending, which affects the final radius.

Calculation:

$$R_{\text{final}} = R_{\text{initial}} \times (1 - \text{springback factor})$$

where springback factor depends on material properties and bending parameters.

Correcting for springback involves over-bending slightly in initial passes.

Roll Gap Adjustment

The initial roll gap must be set considering the plate thickness and the desired final radius.

Approximate formula:

$$\text{Roll gap} = t + \text{allowance}$$

where the allowance accounts for elastic deformation and springback.

Designing a Plate Rolling Process

Effective planning involves integrating all calculations into a comprehensive process.

Step-by-Step Approach

- Identify the plate dimensions and material properties.
- Determine the required curvature or radius.
- Calculate the minimum roll diameter and select appropriate rolls.
- Estimate the bending force needed for the final bend.
- Verify that the machine's capacity exceeds the force requirement with safety margins.
- Plan the number of passes and over-bend to compensate for springback.
- Set the initial roll gap accordingly.
- Perform test bends and adjust parameters based on results.

Documentation:

- Maintain detailed records of all calculations for quality control and repeatability.

Practical Examples and Case Studies

Applying these calculations in real-world scenarios helps solidify understanding.

Example 1: Bending a Steel Plate

Suppose you need to roll a steel plate:

- Material: Structural steel
- Thickness (t) : 20 mm
- Width (b) : 2000 mm
- Desired radius (R) : 3000 mm

Step 1: Calculate the minimum roll diameter:

$$D_{\min} \approx 6 \times t = 6 \times 20 \text{ mm} = 120 \text{ mm}$$

Choose a roll diameter larger than this, say 150 mm.

Step 2: Estimate bending force:

- Young's modulus (E) : 200 GPa
- Permissible stress (σ_{allow}) : $0.6 \times \text{yield strength}$ (assumed 250 MPa), so 150 MPa

$$A = b \times t = 2000 \text{ mm} \times 20 \text{ mm} = 40,000 \text{ mm}^2$$

$$F_{\max} = \sigma_{\text{allow}} \times A = 150 \text{ MPa} \times 40,000 \text{ mm}^2 = 6,000 \text{ kN}$$

This force is quite large, indicating the need for specialized equipment.

Step 3: Determine the number of passes, considering material springback and process constraints.

Conclusion

Calculating parameters for a plate rolling machine is a complex task that combines material science, mechanical engineering, and process planning. Accurate calculations of roll diameter, bending force, and machine capacity are essential to produce high-quality rolled plates efficiently and safely. By understanding the interplay of these factors and applying systematic calculation methods, engineers can optimize the rolling process, select suitable equipment, and prevent failures. As technology advances, integrating software tools and simulation models further enhances the precision and reliability of these calculations, leading to improved productivity and quality in manufacturing operations.

References and Further Reading:

- "Metal Forming: Mechanics and Metallurgy" by William F. Hosford
- "Manufacturing Processes for Engineering Materials" by Serope Kalpakjian and Steven R. Schmid
- Industry standards and guidelines such as ASTM and ISO for material properties and safety factors

Plate Rolling Machine Calculation: An Expert Guide to Precision and Efficiency

In the world of metal fabrication and sheet metal processing, plate rolling machines stand as essential tools for shaping and bending large sheets of metal into cylindrical or curved forms. The efficiency, accuracy, and safety of these machines hinge heavily on precise calculations. Understanding how to perform plate rolling machine calculation is vital for manufacturers, engineers, and operators aiming to optimize production, reduce material waste, and ensure structural integrity.

This comprehensive guide delves into the core principles behind plate rolling machine calculations, covering the fundamental parameters, mathematical formulas, practical considerations, and tips for achieving optimal results. Whether you are a seasoned professional or new to the field, mastering these calculations can significantly enhance your operational outcomes.

Understanding the Basics of Plate Rolling Machines

Before diving into calculations, it's essential to understand the key components and functions of a plate rolling machine.

What Is a Plate Rolling Machine?

A plate rolling machine is a device designed to bend and shape flat metal plates into cylindrical, conical, or curved shapes. It typically consists of three or four rollers arranged in various configurations to facilitate bending.

Key Components

- **Rollers:** The main elements that apply force to the plate.
- **Drive System:** Powers the rollers' rotation.
- **Control Panel:** Allows operators to set parameters such as rotation speed and bend radius.
- **Frame and Support:** Ensures stability during operation.

Types of Plate Rolling Machines

- Three-Roller Plate Rollers: Commonly used for simple bending tasks; consist of two fixed rollers and one movable roller.
- Four-Roller Plate Rollers: Offer better control, especially for complex shapes; include two fixed and two movable rollers.

Fundamental Parameters in Plate Rolling Calculations

Accurate calculations depend on understanding several vital parameters:

- Material Properties
 - Material Thickness (t): The thickness of the plate, usually measured in millimeters or inches.
 - Material Type: Different metals (steel, aluminum, stainless steel) have varying ductility and yield strengths.
 - Young's Modulus (E): Measures the stiffness of the material.
 - Yield Strength (σ_y): The stress at which material begins to deform plastically.
- Roll Dimensions
 - Roll Diameter (Dr): The diameter of the rollers significantly affects the bend radius.
 - Roll Radius (Rr): Half of the diameter ($R_r = D_r/2$).
- Bending Parameters
 - Desired Bend Radius (Rb): The radius of the curvature you intend to achieve.
 - Bending Angle (θ): The angle through which the plate is bent.
 - Number of Passes: Some shapes require multiple passes to reach the final bend.
- Machine Settings

- Roll Gap (g): The space between the rollers, adjustable to control the bend.
- Roll Pressure: The force applied by the rollers to deform the plate.

Calculating the Bend Radius and Plateau Parameters

Achieving the correct bend radius is crucial for ensuring the structural integrity and aesthetic quality of the formed part.

Theoretical Bend Radius Calculation

The theoretical bend radius is primarily determined by the material properties and the roller diameter. A common approximation is:

$$R_b = k \times t$$

where:

- R_b = bend radius
- t = material thickness
- k = a factor depending on material ductility, typically ranging from 1.0 to 3.0

Note: For ductile materials, the bend radius can often be close to the material thickness, but for brittle materials, a larger bend radius is necessary to prevent cracking.

Practical Formula for Bend Radius

A more precise calculation considers the neutral axis shift and the bend allowance:

$$R_b = \frac{t}{\sin(\frac{\theta}{2})}$$

where:

- θ = bend angle in degrees

This formula helps to estimate the bend radius based on the desired angle and material thickness.

Calculating the Roll Force and Power Requirements

Proper calculation of the roll force and power ensures the machine can perform the task without

overloading or risking damage.

Roll Force Calculation

The force required (F) to bend the plate can be estimated using:

$$F = \frac{K \times \sigma_y \times t \times L}{\text{efficiency factor}}$$

where:

- (K) = a factor depending on the bend type (commonly 1.33 for bending)
- (σ_y) = yield strength of the material
- (t) = material thickness
- (L) = the length of the plate being bent
- Efficiency factor accounts for machine and process inefficiencies (typically 0.8 to 1.0)

Example:

For a steel plate with:

- (t = 10\,mm)
- (L = 1000\,mm)
- ($\sigma_y = 350\,\text{MPa}$)
- (K = 1.33)

The force:

$$F = \frac{1.33 \times 350 \times 10 \times 1000}{0.9} \approx 5,167,000\,\text{N}$$

This force informs the selection of suitable rollers and hydraulic systems.

Power Calculation

The power (P) required to perform the bend at a given speed (v) can be calculated as:

$$P = F \times v$$

where:

- v = the linear speed of the plate through the machine (mm/sec)

Adjusting for efficiency and safety margins is vital.

Determining the Optimal Roll Gap and Pass Strategy

The roll gap influences the bending radius and the quality of the bend.

Roll Gap Calculation

A typical formula for the initial roll gap:

$$g_{\text{initial}} = t \times (1 + \text{overbend factor})$$

The overbend factor accounts for the material's elastic recovery and plastic deformation, often ranging from 1.2 to 1.5.

Pass Strategy

Depending on the desired bend radius and material ductility, multiple passes may be necessary. The general approach:

- First Pass: Use a large roll gap to start the bend.
- Subsequent Passes: Gradually decrease the roll gap to reach the final radius.
- Final Pass: Achieve the precise bend angle with minimal residual stress.

Practical Considerations and Tips for Accurate Calculations

While calculations provide a critical foundation, real-world factors often influence the final outcome. Here are key considerations:

Material Variability

- Ductility Variations: Even within the same material grade, ductility can differ based on processing history.
- Surface Conditions: Surface roughness and cleanliness affect friction and bending behavior.

Machine Capabilities

- Maximum Roll Diameter: Ensure calculations do not exceed the machine's physical limits.
- Load Capacity: Confirm the machine can handle the calculated forces comfortably.

Safety Margins

Always include safety margins (typically 10-20%) in force and power calculations to account for unforeseen factors.

Simulation and Testing

- Use finite element analysis (FEA) software for complex shapes.
- Perform test bends on scrap material to verify calculations.

Conclusion: Mastering Plate Rolling Machine Calculation for Optimal Results

Accurate plate rolling machine calculation is a blend of theoretical understanding, practical experience, and iterative testing. By carefully analyzing material properties, machine parameters, and desired outcomes, operators and engineers can plan efficient, precise bends that meet structural and aesthetic requirements.

Key takeaways include:

- Understanding the interplay between material ductility, thickness, and bend radius.
- Calculating the necessary roll force and power to ensure safe and efficient operation.
- Strategically planning passes and adjusting roll gaps for quality results.
- Incorporating safety margins and real-world testing into the calculation process.

In the rapidly evolving landscape of metal fabrication, mastery of these calculations empowers professionals to push the boundaries of design and manufacturing while maintaining safety and efficiency. Whether producing large industrial components or intricate artistic sculptures, precise calculations are the backbone of successful plate rolling operations.

Question What are the key parameters to consider when calculating the capacity of a plate rolling machine? The key parameters include the machine's maximum plate thickness, width, bending radius, and the material's properties such as yield strength and ductility. These factors help determine the maximum plate size and thickness the machine can handle safely and effectively. **Answer** How do you calculate the bending radius for a plate rolling process? The bending radius is typically calculated based on the plate thickness and the desired curvature, using the formula $R = (t / (1 - k))$,

where R is the radius, t is the plate thickness, and k is a factor depending on material properties and roll geometry. Manufacturers often provide recommended bending radii for specific thicknesses and materials. What is the formula to determine the roll force in a plate rolling machine? The roll force can be estimated using the formula: $F = (\sigma_y \times t \times W) / (\cos(\alpha))$, where σ_y is the material's yield strength, t is the plate thickness, W is the width of the plate, and α is the roll angle. Accurate calculation may require more detailed analysis considering friction and machine leverage. How can I estimate the minimum sheet thickness that can be rolled without causing material failure? Estimate the minimum thickness based on the material's ductility and the maximum achievable bending radius. Use the empirical relation $t_{\min} = (R \times \sigma_y) / (E)$, where σ_y is yield strength and E is the modulus of elasticity. Always ensure the process stays within safe limits to prevent cracking or deformation. What considerations are important when calculating the required motor power for a plate rolling machine? Motor power calculation involves estimating the roll force, the roll diameter, and the process speed. The formula $P = (F \times v) / \eta$, where F is the roll force, v is the roll velocity, and η is the efficiency, helps determine the required power. Factors like friction, material properties, and safety margins should also be considered. How do material properties influence the calculations for plate rolling machine setup? Material properties such as yield strength, ductility, and Young's modulus impact the bending radius, roll force, and deformation behavior. Knowing these properties allows for accurate calculations to prevent material failure and optimize rolling parameters. Are there industry-standard formulas or software for calculating plate rolling machine parameters? Yes, industry standards from organizations like ASTM and ISO provide guidelines, and specialized software tools are available for precise calculations. These tools incorporate material data, machine specifications, and process variables to optimize setup and ensure safety and efficiency.

Related keywords: plate rolling machine, roll bending calculation, sheet metal forming, curvature calculation, bend radius, roll diameter, material properties, stress analysis, machine capacity, deformation modeling